

圧着端子加工

品番	使用ワイヤー	ϕd_2	B	L	F	E	ϕD	T
R1.25-3	$\phi 0.63 \sim \phi 1.5$	$\phi 3.2$	5.5	11.5	4.0	4.8	3.4	0.8
R1.25-3.5	$\phi 0.63 \sim \phi 1.5$	$\phi 3.7$	6.6	14.4	6.3	4.8	3.4	0.8
R1.25-3.7	$\phi 0.63 \sim \phi 1.5$	$\phi 3.7$	5.5	11.5	4.0	4.8	3.4	0.8
R1.25-8	$\phi 0.63 \sim \phi 1.5$	$\phi 8.4$	11.6	21.7	11.1	4.8	3.4	0.8
R2-4	$\phi 0.63 \sim \phi 2.0$	$\phi 4.3$	8.5	16.8	7.8	4.8	4.1	0.8
R2-5	$\phi 0.63 \sim \phi 2.0$	$\phi 5.3$	9.5	16.8	7.3	4.8	4.1	0.8
R2-6	$\phi 0.63 \sim \phi 2.0$	$\phi 6.4$	12	21.8	11	4.8	4.1	0.8
R5.5-5	$\phi 0.63 \sim \phi 3.0$	$\phi 5.3$	9.5	19.8	8.3	6.8	5.6	1.0

材質：銅
表面処理：スズメッキ

